

## Emergency Only Call Point, Button Reset

Part No. **NC804DE**



### Overview

- A button-operated call/reset point capable of generating Emergency calls on an 800 Series Call System.
- Onboard reset button cancels Emergency calls made from the NC804DE **and** Standard calls made from other devices wired on the same zone (such as ceiling pull units in Ensuite areas).
- Ideal for use as a reset point for ceiling pull units that will allow a more urgent Emergency call to be made if additional assistance is required.
- Red reassurance LED confirms a call has been made.
- Mounts on a standard UK 25mm single gang flush or surface back box.



### More Information

### Technical Specifications

Quiescent current	0mA (none).
Alarm current	Determined by the type of control equipment and number / type of field devices connected to the system.
Indicators	Red Reassurance LED (lit intermittently for Emergency calls made on the NC804DE and constantly for Standard calls made from other devices on the same zone).
Controls	Alert button (generates Emergency calls); Reset button (cancels Emergency calls from the NC804DE or Standard calls from devices wired on the same Zone).
Connections	SIG (Signal); -Ve (Negative); +Ve (Positive).



Onboard 6.35mm Remote Jack Socket	No.
Onboard Infrared Receiver	No.
Product dimensions (mm)	87 W x 87 H x 24 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish	Plastic.
IP Rating	IP40.
Weight	58g
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.



T 01942 322744 E sales@c-tec.co.uk  
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom