

Magnetic Reset Point

Part No. **NC809DM**



Overview

- A magnetic key-operated reset point for use with C-TEC's 800 Series Call System.
- Can be used to remotely and securely cancel standard calls generated from ceiling pulls and/or wall call points that are wired on the same zone.
- Magnetic reset 'target' requires a separately available NC803M magnetic reset key to operate.
- Mounts on a standard UK 25mm single gang flush or surface back box.



More Information

Technical Specifications

Quiescent current	0mA (none).
Alarm current	Determined by the type of control equipment and number / type of field devices connected to the system.
Controls	Magnetic reset target (cancels Standard calls from any device wired on the same Zone). Reset operation requires an NC803M magnetic reset key.
Connections	SIG (Signal); -Ve (Negative); RC (connected to Signal)
Product dimensions (mm)	87 W x 87 H x 24 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish	Plastic.
IP Rating	IP41.
Weight	58g



Operating conditions/temperature -5°C to +40°C. Max. relative humidity 95% non-condensing.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom