

Quantec Addressable Infrared Ceiling Receiver (Round Version)

Part No. **QT302RXX**



Overview

- An unobtrusive addressable Infrared Ceiling Receiver for use with our Quantec or Quantec-Pro call systems.
- Designed to accept infrared calls from compatible Quantec staff attack transmitters, patient neck/wrist pendants and staff attendance pendants.
- Typically used in bedrooms, corridors, common rooms and any other area requiring infrared coverage.
- Includes a red confidence light.
- Typical 10m line of sight receiving range.
- Up to three QT302RXRS extender infrared receivers can be connected to an addressable ceiling receiver to increase IR coverage.
- Optional QT848/10 locking kit, complete with 10 grub screws and Allen key, also available.



More Information

Technical Specifications

Power requirements	TBC.
Quiescent current	TBC.
Indicators	Red/green confidence LED/diffuser.
Controls	n/a.
Connections	N+: N-; R; G; L+; IR



Expansion connections	R; G; IR; N+ and N- terminals allow the connection of optional dummy/extender overdoor lights and dummy/extender infrared receivers.
Onboard 6.35mm Remote Jack Socket	No.
Onboard Sounder	No,
Onboard Infrared Receiver	Yes - will accept calls from compatible Quantec infrared transmitters.
Product dimensions (mm)	81mm diameter x 27mm deep. Designed for ceiling mounting only. Base fits 16mm conduit and BESA centres.
Construction & finish	White round plastic.
IP Rating	TBC.
Weight	42g
Operating conditions/temperature	-5°C to +40°C. Max relative humidity: 95%.
Notes	Optional QT848/10 locking kit, complete with 10 grubscrews and Allen key, available.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom