

## DS-2CD2T83G2-2I/4I 8 MP AcuSense Fixed Bullet Network Camera

AcuSense



Empowered by deep learning algorithms, Hikvision AcuSense technology brings human and vehicle targets classification alarms to front- and back-end devices. The system focuses on human and vehicle targets, vastly improving alarm efficiency and effectiveness.

- High quality imaging with 8 MP resolution
- Efficient H.265+ compression technology
- Clear imaging against strong backlight due to 120 dB WDR technology
- Focusing on human and vehicle classification based on deep learning
- Water and dust resistant (IP67)



## ▪ Specification

| Camera                 |                                                                                                                                                                                                   |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Image Sensor           | 1/2.8" Progressive Scan CMOS                                                                                                                                                                      |
| Min. Illumination      | Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR                                                                                                                                             |
| Shutter Speed          | 1/3 s to 1/100,000 s                                                                                                                                                                              |
| Slow Shutter           | Yes                                                                                                                                                                                               |
| P/N                    | P/N                                                                                                                                                                                               |
| Wide Dynamic Range     | 120 dB                                                                                                                                                                                            |
| Day & Night            | IR cut filter                                                                                                                                                                                     |
| Angle Adjustment       | Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°                                                                                                                                              |
| Lens                   |                                                                                                                                                                                                   |
| Lens Type              | Fixed focal lens, 2.8, 4, and 6 mm optional                                                                                                                                                       |
| Focal Length & FOV     | 2.8 mm, horizontal FOV 107°, vertical FOV 57°, diagonal FOV 128°<br>4 mm, horizontal FOV 87°, vertical FOV 46°, diagonal FOV 105°<br>6 mm, horizontal FOV 54°, vertical FOV 29°, diagonal FOV 63° |
| Lens Mount             | M12                                                                                                                                                                                               |
| Iris Type              | Fixed                                                                                                                                                                                             |
| Aperture               | F1.6                                                                                                                                                                                              |
| DORI                   |                                                                                                                                                                                                   |
| DORI                   | 2.8 mm: D: 88 m, O: 35 m, R: 17 m, I: 9 m<br>4 mm: D: 108 m, O: 43 m, R: 22 m, I: 11 m<br>6 mm: D: 177 m, O: 70 m, R: 35 m, I: 18 m                                                               |
| Illuminator            |                                                                                                                                                                                                   |
| Supplement Light Type  | IR                                                                                                                                                                                                |
| Smart Supplement Light | Yes                                                                                                                                                                                               |
| IR Wavelength          | 850 nm                                                                                                                                                                                            |
| IR Range               | -2I: up to 60 m<br>-4I: up to 80 m                                                                                                                                                                |
| Video                  |                                                                                                                                                                                                   |
| Max. Resolution        | 3840 × 2160                                                                                                                                                                                       |
| Main Stream            | 50 Hz: 20 fps (3840 × 2160)<br>25 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)<br>60 Hz: 20 fps (3840 × 2160)<br>30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)            |
| Sub Stream             | 50 Hz: 25 fps (640 × 480, 640 × 360)<br>60 Hz: 30 fps (640 × 480, 640 × 360)                                                                                                                      |
| Third Stream           | 50 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)<br>60 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)<br>*Third stream is supported under certain settings.              |
| Video Compression      | Main stream: H.265/H.264/H.264+/H.265+<br>Sub-stream: H.265/H.264/MJPEG<br>Third stream: H.265/H.264<br>*Third stream is supported under certain settings.                                        |
| Video Bit Rate         | 32 Kbps to 16 Mbps                                                                                                                                                                                |

|                               |                                                                                                                                                                                                                                  |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| H.264 Type                    | Baseline Profile/Main Profile/High Profile                                                                                                                                                                                       |
| H.265 Type                    | Main Profile                                                                                                                                                                                                                     |
| H.264+                        | Main stream supports                                                                                                                                                                                                             |
| H.265+                        | Main stream supports                                                                                                                                                                                                             |
| Bit Rate Control              | CBR/VBR                                                                                                                                                                                                                          |
| Scalable Video Coding (SVC)   | H.264 and H.265 encoding                                                                                                                                                                                                         |
| Region of Interest (ROI)      | 1 fixed region for main stream and sub-stream                                                                                                                                                                                    |
| <b>Network</b>                |                                                                                                                                                                                                                                  |
| Protocols                     | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP                                                                                   |
| Simultaneous Live View        | Up to 6 channels                                                                                                                                                                                                                 |
| API                           | Open Network Video Interface (Profile S, Profile G), ISAPI, SDK                                                                                                                                                                  |
| User/Host                     | Up to 32 users. 3 user levels: administrator, operator and user                                                                                                                                                                  |
| Security                      | Password protection, complicated password, HTTPS encryption, IP address filter, Security Audit Log, basic and digest authentication for HTTP/HTTPS, TLS 1.1/1.2, WSSE and digest authentication for Open Network Video Interface |
| Network Storage               | NAS (NFS, SMB/CIFS), auto network replenishment (ANR)                                                                                                                                                                            |
| Client                        | iVMS-4200, Hik-Connect, Hik-Central                                                                                                                                                                                              |
| Web Browser                   | Plug-in required live view: IE 10, IE 11<br>Plug-in free live view : Chrome 57.0+, Firefox 52.0+<br>Local service: Chrome 57.0+, Firefox 52.0+                                                                                   |
| <b>Image</b>                  |                                                                                                                                                                                                                                  |
| Image Parameters Switch       | Yes                                                                                                                                                                                                                              |
| Image Settings                | Rotate, mirror, privacy mask, saturation, brightness, contrast, sharpness, gain, white balance adjustable by client software or web browser                                                                                      |
| Day/Night Switch              | Day, Night, Auto, Schedule                                                                                                                                                                                                       |
| Image Enhancement             | BLC, HLC, 3D DNR                                                                                                                                                                                                                 |
| SNR                           | ≥ 52 dB                                                                                                                                                                                                                          |
| <b>Interface</b>              |                                                                                                                                                                                                                                  |
| Ethernet Interface            | 1 RJ45 10 M/100 M self-adaptive Ethernet port                                                                                                                                                                                    |
| On-board Storage              | Built-in memory card slot, support micro SD card, up to 256 GB                                                                                                                                                                   |
| Hardware Reset                | Yes                                                                                                                                                                                                                              |
| <b>Event</b>                  |                                                                                                                                                                                                                                  |
| Basic Event                   | Motion detection (human and vehicle targets classification), video tampering alarm, exception                                                                                                                                    |
| Face Detection                | Yes                                                                                                                                                                                                                              |
| <b>Deep Learning Function</b> |                                                                                                                                                                                                                                  |
| Perimeter Protection          | Line crossing detection, intrusion detection<br>Supports human and vehicle targets classification                                                                                                                                |
| <b>General</b>                |                                                                                                                                                                                                                                  |
| Linkage Method                | Upload to FTP/memory card/NAS, notify surveillance center, trigger recording, trigger capture, send email                                                                                                                        |
| Camera Material               | Aluminum alloy body<br>Sun shield, IR cover: plastic                                                                                                                                                                             |
| Camera Dimension              | Ø105 mm × 293 mm (Ø4.13" × 11.53")                                                                                                                                                                                               |


|                                  |                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Package Dimension                | 386 mm × 156 mm × 155 mm (15.2" × 6.2" × 6.2")                                                                                                                                                                                                                                                                                                          |
| Camera Weight                    | Approx. 1090 g (2.4 lb.)                                                                                                                                                                                                                                                                                                                                |
| With Package Weight              | Approx. 1590 g (3.5 lb.)                                                                                                                                                                                                                                                                                                                                |
| Storage Conditions               | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)                                                                                                                                                                                                                                                                               |
| Startup and Operating Conditions | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)                                                                                                                                                                                                                                                                               |
| Web Client Language              | 33 languages<br>English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil), Ukrainian |
| General Function                 | Anti-flicker, heartbeat, password reset via email, pixel counter                                                                                                                                                                                                                                                                                        |
| Firmware Version                 | V5.5.113                                                                                                                                                                                                                                                                                                                                                |
| Software Reset                   | Yes                                                                                                                                                                                                                                                                                                                                                     |
| Power Consumption and Current    | -2I:<br>12 VDC, 0.67 A, max. 8.0W<br>PoE (802.3af, 36 V to 57 V), 0.25 A to 0.16 A, max. 9.0 W<br>-4I:<br>12 VDC, 0.92 A, max. 11.0 W<br>PoE (802.3af, 36 V to 57 V), 0.35 A to 0.22 A, max. 12.5 W                                                                                                                                                     |
| Power Supply                     | 12 VDC ± 25%, reverse polarity protection<br>PoE: 802.3af, Class 3                                                                                                                                                                                                                                                                                      |
| Power Interface                  | Ø5.5 mm coaxial power plug                                                                                                                                                                                                                                                                                                                              |
| <b>Approval</b>                  |                                                                                                                                                                                                                                                                                                                                                         |
| EMC                              | FCC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 50130-4: 2011 +A1: 2014); RCM (AS/NZS CISPR 32: 2015); IC (ICES-003: Issue 6, 2016); KC (KN 32: 2015, KN 35: 2015)                                                                                                                                  |
| Safety                           | UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013); CE-LVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013)                                                                                                                                                                                                                                        |
| Environment                      | CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)                                                                                                                                                                                                                                                                           |
| Protection                       | IP67 (IEC 60529-2013)                                                                                                                                                                                                                                                                                                                                   |

#### ▪ Available Model

DS-2CD2T83G2-2I (2.8/4/6 mm)

DS-2CD2T83G2-4I (2.8/4/6 mm)

## ▪ Dimension



## ▪ Accessory

### ▪ Optional

| DS-1275ZJ                                                                           | DS-1297ZJ                                                                           | DS-1297ZJ-ES                                                                        | DS-1232ZJ-T                                                                           | DS-1292ZJ                                                                             |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Vertical Pole Mount                                                                 | Pendant Mount                                                                       | Pendant Mount                                                                       | Cardan Joint                                                                          | Wall Mount                                                                            |
|  |  |  |  |  |

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com